





## STANDARD AIR RETURN:

- A- STANDARD WALL HEIGHT: 106"
- B- AIR RETURN WIDTH: 48"
- C- AIR RETURN DEPTH: 6"
- NOMINAL CAPACITY UP TO 1800 CFM.

## **OPTIONAL AIR RETURN SIZES**

TYPICAL AIR RETURN SIZE (DIMENSION A: AIR RETURN WIDTH)	GRILLE (ACTIVE W	SIZE E FACE) H	CAPACITY (CFM)
12"	10"	12"	500
24"	22"	12"	1,000
36" *	32"	12"	1,500

\*MAXIMUM WIDTH FOR A SINGLE AIR RETURN ALONG A STRAIGHT SECTION OF WALL.

## GENERAL NOTES:

- STATIC PRESSURE AT TOP OF WALL
   (NOT INCLUDING TAKE-OFF COLLAR),
   APPROXIMATELY 0.15" WG
- THE OPTIONAL AIR RETURNS ARE ALSO AVAILABLE AS SHOWN IN DETAIL A.
   i.e. LOCATED WHERE REQUIRED ALONG STRAIGHT WALL SECTION.
- 3. THESE FULL HEIGHT AIR RETURNS MAY ALSO BE USED AS LARGE SERVICE CHASES OR TO CLOSE AROUND COLUMNS.

## NOTES FOR STANDARD AIR RETURNS:

- ALL EXPOSED SURFACES FINISHED IN 2 COAT PPG DURANAR, (COLOUR: WHITE) TO PROVIDE OPTIMUM HARDNESS, MAR-RESISTANCE AND CHEMICAL RESISTANCE.
- 2. PANEL DIMENSIONS:
- HEIGHT: TO SUIT
- PANEL WIDTH: MAXIMUM 48"
- PANEL THICKNESS: STANDARD 1/4"

PEVISIONS					
REV	DESCRIPTION	DATE	DRAWN		
1	ORIGINAL ISSUE		P Mc		
2	GENERAL REVIEW/NEW TITLE BLOCK	08 AUG 05	P.F.		
3	GENERAL REVIEW	SEPT 05	M.L.		
4	NEW LAYOUT	MAY 06	P.F.		

MICROZONE
SE HARRY DOUGLS DRIFE, OTTAINA, ON TAID, CANADA KS 2C7
TEL: (613) 631-6316 www.infactor.com FAX (613) 431-6311

INTRODUCTION TO MODULAR
CLEANROOMS AND CONTAINMENT
FACILITY SYSTEMS

FULL HEIGHT AIR RETURN/SERVICE CHASE: FLUSH TYPE AND STANDARD TYPE

E-FILE: CRW3-10 dwo