



NOTES:

1. **AUTOMATIC CLEANROOM SLIDING DOOR:** DOOR HEADER, JAMBS AND DOOR PANEL FRAMES ARE CONSTRUCTED OF ANODIZED ALUMINUM. GLASS IS 1/4" THICK AND IS SET INTO BEVELLED ANODIZED ALUMINUM PROFILES. GLASS TINTED AS REQUIRED.

2. **DOOR PACKAGE SIZES:**

PACKAGE HEIGHT: TO SUIT

WIDTH:	CLEAR DOOR OPENING:	EMERG. BREAKOUT
7'-0"	36"	39"
8'-0"	42"	45"
9'-0"	48"	51"

CUSTOM WIDTH PACKAGES AVAILABLE TO SUIT

3. **DOOR PACKAGES AVAILABLE IN SINGLE-SLIDE OR BI-PART FORMAT**

4. **SLIDING DOORS ARE EQUIPPED WITH MICROWAVE MOTION SENSORS & INFRARED THRESHOLD PRESENCE SAFETY SENSORS**

5. **CLEANROOM SLIDING DOOR OPERATION IS FAIL-SAFE**

6. **SLIDING DOORS CAN BE INTERLOCKED EITHER WITH OTHER SLIDING DOORS OR REGULAR SWING TYPE CLEANROOM DOORS.**

7. **OPTIONAL FLY-OPEN BOX IS TIED INTO BUILDING FIRE ALARM SYSTEM AND EMERGENCY POWER. IN THE EVENT THE BUILDING FIRE ALARM IS ACTIVATED, THE SLIDING DOOR WILL OPEN AUTOMATICALLY.**

8. **AUTOMATIC SLIDING DOORS CAN BE ACTIVATED BY CARD READER DEVICES (SUPPLIED AND INSTALLED BY OTHERS)**

1	ORIGINAL ISSUE	17 APR 06	PF
REV	DESCRIPTION	DATE	DRAWN
REVISIONS			



INTRODUCTION TO MODULAR CLEANROOMS AND CONTAINMENT FACILITY SYSTEMS

Drawing Title: **CLEANROOM AUTOMATIC SLIDING DOOR**

Drawn By: PF	Checked By:	Scale: AS NOTED	Date: 17 APR. 06
Issue: - - - -	Job Number:	Drawing Number: CRW3-16A	Quantity: - -

UNLESS OTHERWISE NOTED, THIS DRAWING REMAINS THE PROPERTY OF MICROZONE CORPORATION. IT SHALL NOT BE REPRODUCED OR USED FOR MANUFACTURE, DESIGN OR CONSTRUCTION WITHOUT THE EXPRESS WRITTEN AUTHORIZATION BY THE OWNER. THE ACCEPTOR, BY ACCEPTING THIS DRAWING, ASSUMES THE CUSTODY THEREOF, AND UNDER THE ABOVE TERMS AGREES NOT TO ALLOW ITS USE BY UNAUTHORIZED PERSONS, WITHOUT INCURRING LIABILITY FOR FINES, PENALTIES BY LAW.